# BXP01 Series
# Explosion-proof Emergency Box



Ex mark: Ex db IIC T6 Gb
Ex tb IIIC T80℃ Db, IP66



## Application

- Low installation height equipment area like petrochemical plants, chemical plants, pharmaceutical factory, polishing plant, etc.

## Characteristics

- The junction box has the characteristics of small volume, light weight, convenient installation, etc.
- The shell adopts anti-corrosive processing, standard for the 304 stainless steel material, using high-tech surface anti-corrosion treatment technology, applicable to all kinds of bad industrial environment.

## Main Specification

| Item | Technical Parameter |
|---|---|
| Input voltage (V) | 90~264VAC |
| Rated frequency | 50Hz / 60Hz |
| Life time (h) | 6000 |
| Rated capacity | 2.6Ah/14.8V |
| Cable entry | M20×1.5, M25×1.5, NPT3/4", NPT1/2", G3/4" |
| Dimension (mm) | 238×222×106 |
| Net weight (kg) | 2.9 |

## Ordering Reference

| Model number | Rated wattage (W) | Emergency duration (min) |
|---|---|---|
| BXP01 | 10W | >140min |
| | 20W | >70min |
| | 30W | >45min |

## Drawing of Dimension (Dimensions in mm)

