TORMIN Industrial Fixed Lights

ZY5320 LED Tri-Proof Light (Single tube)

Wattage	9W	18W
Rated Vol.	220VAC	
IP Code	IP66	
Weight	1.0kg	1.6kg
Size	655×75×86mm	1265×75×86mm

ZY5320 LED Tri-Proof Light (Double tubes)

Wattage	2×9W	2×18W
Rated Vol.	220VAC	
IP Code	IP66	
Weight	1.5kg	2.3kg
Size	655×113×86mm	1265×113×86mm

ZY5322B LED Flood Light

Wattage	30W 40W	60W 80W
Rated Vol.	100~240VAC(200~240VAC for 80W)	
IP Code	IP66	
Weight	3.2kg/3.4kg	4.5kg/4.7kg
Size	700×182×68mm	1150×182×68mm

ZY5323A LED Clean Light

Wattage	12W 18W 24W 36W 40W	24W 36W 48W 60W 80W
Rated Vol.	220VAC	
IP Code	IP66	
Weight	2.3kg	4.3kg
Size	300×600×15mm	300×1200×15mm

ZY5323B LED Clean Light

Wattage	24W 36W
Rated Vol.	220VAC
IP Code	IP66
Weight	4. 3kg
Size	600×600×15mm

ZY8102F LED Flood Light

Wattage	80W 100W 120W 150W 180W 240W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	5.2kg (2 Modules); add 1pcs Module add 1kg
Size	L322×363×150mm(2 Modules) Add 1 Module, Length add 78mm

ZY8102D LED Flood Light

Wattage	50W 100W 150W 200W 250W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	3.3kg(1 Module); add 1pcs Module add 0.7Kg
Size	315×L193×130mm(1 Module) Add 1 Module, Length add 45mm

ZY8102D LED Flood Light

Wattage	300W	400W
Rated Vol.	100~277VAC	
IP Code	IP66	
Weight	8.1kg	9. 7kg
Size	599×283×130mm	599×360×130mm

ZY8106 LED Light

Wattage	50W 100W 150W 200W
Rated Vol.	100~240VAC
IP Code	IP66
Weight	3.5kg(100W)Watt add 50W,weight add 1.3kg
Size	L403×W295×80mm(100W) Watt add 50W, L add 29mm, W add 32.5mm

ZY8507B LED High Bay Light

Wattage	50W 100W 150W 200W 250W
Rated Vol.	100~240VAC
IP Code	IP66
Weight	2.9kg(50W) Watt add 50W,weight add 0.8kg
Size	ϕ353×270mm(50W) Watt add 50W, H add 40mm

ZY8507A LED High Bay Light

Wattage	300W	400W
Rated Vol.	100~240VAC	
IP Code	IP66	
Weight	7.2kg	8.1kg
Size	ϕ353×500mm	ϕ353×560mm

ZY8509B LED High Bay Light

Wattage	50W 80W 100W 120W 150W	200W
Rated Vol.	100~277VAC/DC	
IP Code	IP66	
Weight	2.5kg	3kg
Size	ϕ370×175mm	ϕ450×200mm

ZY8601P LED Light

Wattage	30W 40W 50W 60W	80W
Rated Vol.	100~240VAC	
IP Code	IP66	
Weight	2.2kg	2.7kg
Size	ϕ230×167mm	ϕ240×195mm

ZY8601S LED Light

Wattage	30W 40W 50W 60W	80W
Rated Vol.	100~240VAC	
IP Code	IP66	
Weight	3kg	3.5kg
Size	270×250×167mm	275×270×195mm

ZY8702 LED Street Light

Wattage	60W 80W 100W 120W 150W 180W 240W
Rated Vol.	100~277VAC
IP Code	IP65
Weight	6.5kg(2 Modules); Add 1 module, add 1kg
Size	520(L)×315×100mm(2 Modules) Add 1 module, L add 95mm

ZY8707A Street Light

Wattage	60W 80W 100W 120W 150W
Rated Vol.	100~240VAC
IP Code	IP65
Weight	6.5kg
Size	880×400×180mm

ZY8108 LED Light

Wattage	30W 40W 50W 60W 80W 100W 120W 150W	200W 240W 300W	400W 600W
Rated Vol.	100~240VAC		
IP Code	IP66		
Weight	5kg	10.3kg	20kg
Size	330×273×111mm	350×502×111mm	675×548×111mm

ZY5321 LED Tri-proof Light

Wattage	18W	36W	48W
Rated Vol.	220VAC		
IP Code	IP66		
Weight	0.72kg	1.2kg	1.5kg
Size	656×75×72mm	1256×75×72mm	1556×75×72mm

ZY8502A LED High Bay Light

Wattage	80W 100W 120W	150W 200W	250W
Rated Vol.	100~277VAC		
IP Code	IP65		
Weight	4.1kg	4.5kg	5.1kg
Size	ϕ300×182mm	ϕ340×182mm	ϕ380×182mm

ZY8502B LED High Bay Light

Wattage	80W 100W 120W	150W 200W
Rated Vol.	100~277VAC	
IP Code	IP65	
Weight	4.1kg	4.5kg
Size	ϕ300×182mm	ϕ340×182mm

ZY8605A LED Light

Wattage	80W 100W 120W	150W 200W	250W
Rated Vol.	100~277VAC		
IP Code	IP65		
Weight	5.3kg	5.7kg	6.3kg
Size	332×340×130mm	352×360×130mm	392×400×130mm

ZY8605B LED Light

Wattage	80W 100W 120W	150W 200W
Rated Vol.	100~277VAC	
IP Code	IP65	
Weight	5.3kg	5.7kg
Size	332×340×238mm	352×360×238mm

ZM1100 LED Downlight

Wattage	5W 7W	9W 12W
Rated Vol.	220VAC	
IP Code	IP42	
Spec	2.5"/3"/3.5"/4"	
Weight	0.2kg	0.3kg
Size	ϕ100×47mm	ϕ143×57mm

ZM1200A LED Panel Light

Wattage	18W	36W	48W
Rated Vol.	100~240VAC		
IP Code	IP20		
Weight	1.5kg	3.2kg	6.3kg
Size	600×300×11mm	1200×300×11mm	1200×600×11mm

ZM1200B LED Panel Light

Wattage	18W	36W
Rated Vol.	100~240VAC	
IP Code	IP20	
Weight	0.95kg	3. 1kg
Size	300×300×11mm	600×600×11mm

ZM1400 LED Bulb

Wattage	5W	7W
Rated Vol.	220VAC	
Weight	0. 1kg	0. 15kg
Size	50×96mm	60×119mm

ZM1500 Single Ended T8 LED Tube / Double Ended T8 LED Tube

Wattage	8W	16W
Rated Vol.	220VAC	
Weight	0.1kg	0.2kg
Size	600×ϕ30mm	1200×ϕ30mm

ZM1500 Bracket Light Bracket

Wattage	16W	2×16W
Rated Vol.	220VAC	
Weight	0.45kg	0.85kg
Size	600×ϕ30mm	1200×ϕ30mm

ZY2000 LED Light source

Wattage	30W 40W 50W 60W
Rated Vol.	220VAC/DC
Weight	0.85kg
Size	ϕ177×194mm

ZY5302 LED Tri-proof Light

Wattage	12W 14W 24W
Rated Vol.	220VAC
IP Code	IP65
Weight	0.7kg
Size	ϕ260×126mm

ZY5322E LED Tri-proof Light

Wattage	20W 30W	40W 50W 60W
Rated Vol.	220VAC	
IP Code	IP66	
Weight	2kg	3kg
Size	590×182×68mm	1040×182×68mm

ZY8101 LED Flood Light

Wattage	25W 40W 60W 80W
Rated Vol.	100~240V/24V/36VAC/DC
IP Code	IP66
Weight	4.7kg
Size	300×300×75mm

ZY8303S LED Sight Hole Light

Wattage	10W 20W
Rated Vol.	220V/12V/24V/36VAC/DC
Switch Mode	Regular /Delay switch
IP Code	IP66
Weight	1.3kg
Size	ϕ105×144mm

ZY8303Z LED Sight Hole Light

Wattage	10W 20W
Rated Vol.	220V/12V/24V/36VAC/DC
Switch Mode	Regular /Delay switch
IP Code	IP66
Weight	1.3kg
Size	105×138×144mm

ZY8501A LED Surface Mounted Downlight

Wattage	50W	100W
Rated Vol.	100~240V AC	
IP Code	IP65	
Weight	1.5kg	1.85kg
Size	ϕ203*222mm/ϕ232*226mm	

ZY8501B LED Surface Mounted Downlight

Wattage	50W	100W
Rated Vol.	100~277V AC	
IP Code	IP65	
Weight	2.4kg	3.2kg
Size	ϕ183x175mm	ϕ183x258mm

ZY8503 LED Canopy Light

Wattage	80W 100W 120W
Rated Vol.	100~240VAC/DC
IP Code	IP66
Weight	7.9kg
Size	415×415×91mm

ZY8603S LED Light

Wattage	30W 40W 50W 60W 80W
Rated Vol.	100~277V/24V/36VAC/DC
IP Code	IP66
Weight	4.9kg
Size	245×260×270mm

ZY8605S LED Light

Wattage	100W 120W 150W 200W 240W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	7. 5kg
Size	295×330×350mm

ZY8606S LED Light

Wattage	240W 300W 400W 480W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	13kg
Size	602×340×250mm

ZY8606SC LED Light (Special for Bridge Crane)

Wattage	240W 300W 400W 480W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	15kg
Size	602×300×440mm

ZY8606SH LED Light (High Pole Light)

Wattage	240W 300W 400W 480W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	13kg
Size	602×415×255mm

ZY8607S LED Light

Wattage	30W 40W 50W 60W 80W
Rated Vol.	100~240V/24V/36VAC/DC
IP Code	IP66
Weight	3.7kg
Size	180×230×270mm

ZY8800 LED Light

Wattage	6W 12W 20W
Rated Vol.	100~240V/24V/36VAC/DC
IP Code	IP66
Weight	1kg
Size	180×130×66mm

ZY9710 High Power LED Light

Wattage	100W 120W 150W 200W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	6.3kg
Size	ϕ300×202×332mm

ZY8705 LED Street Light

Wattage	50W 80W 100W	120W 150W
Rated Vol.	100~240VAC	
IP Code	Ip65	
Weight	4.4kg	6kg
Size	664×243×96mm	719×297×96mm

ZY8508 LED High Bay light

Wattage	80W	100W	150W	200W	300W
Rated Vol.	100~240VAC/DC				
IP Code	IP66				
Weight	1.2kg	2.1kg	3kg	3.1kg	5.3kg
Size	ϕ230×122mm	ϕ270×183mm	ϕ330×193mm	ϕ280×203mm	ϕ422×220mm

ZY8610 LED Floodlight

Wattage	500W	750W	1000W	1250W	1500W
Rated Vol.	100~277VAC				
IP Code	IP66				
Weight	13.8kg	17.2kg	22kg	26.7kg	31.3kg
Size	625×395×175mm	625×535×175mm	625×625×175mm	625×815×175mm	625×955×175mm

TORMIN Explosion Proof Emergency Lights

■ suitable for explosive gas environment of raw material,like fine chemical industry, electronics microelectronics production,clean room, laboratory, operating room.

■ EX Mark: Ex nR IIC T6 Gc
■ Cable Entry: G3/4 ″ ,NPT3/4″ ,M25×1.5

Ex

BC5404J

Type	Rated voltage (V)	Wattage (W)	emergency wattage(W)	emergency light output(lm)	emergency duration(min)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC5404AJ-L24-L5	100~240VAC	24W	5W	550	≥180	4.3(light)+ 2.9(Emergency box)	zone2	300×600	48W
BC5404AJ-L36-L5		36W							72W
BC5404AJ-L48-L5		48W							96W
BC5404BJ-L24-L5		24W						1200×300	48W
BC5404BJ-L36-L5		36W							72W
BC5404BJ-L48-L5		48W							96W
BC5404CJ-L24-L5		24W				2.3(light)+ 2.9(Emergency box)		600×600	48W
BC5404CJ-L36-L5		36W							72W
BC5404CJ-L48-L5		48W							96W

■ suitable for explosive gas environment of raw material,like fine chemical industry, electronics microelectronics production,clean room, laboratory, operating room.

■ EX Mark: Ex db mb IIC T6 Gb
■ Cable Entry: G3/4 ″ ,NPT3/4″ ,M25×1.5

Ex

BC5405J

Type	Rated voltage (V)	Wattage (W)	emergency wattage(W)	emergency light output(lm)	emergency duration(min)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC5405AJ-L24-L5	100~240VAC	24W	5W	550	≥180	4.3(light)+ 2.9(Emergency box)	zone2	300×600	48W
BC5405BJ-L24-L5		24W						1200×300	48W
BC5405BJ-L36-L5		36W							72W
BC5405BJ-L48-L5		48W							96W
BC5405CJ-L24-L5		24W				2.3(light)+ 2.9(Emergency box)		600×600	48W
BC5405CJ-L36-L5		36W							72W
BC5405CJ-L48-L5		48W							96W

*Option to use only the emergency function

■ Low height region of pedestrian intensive, like offshore oil, chemical device platform, oil tankers of various channels, cabin, etc.

■ EX Mark: Ex II 2G Ex d e op is IIC T5 Gb
Ex II 2D Ex op is tb IIIC T95℃ Db IP66
■ Cable Entry: M25×1.5, NPT3/4", G3/4"(Standard);
M20×1.5, NPT1/2"
(attached with adaptor)

Ex IECEx Ta 55 Ta -25 IP 66

BC5401 (Emergency)

Type	Rated voltage (V)	Wattage (W)	Emergency wattage (W)	Light output (lm)	Emergency duration (min)	Net weight (kg)	Application	Size (mm)	Replaces Fluorescent lamp
BC5401-L2×10	100~240VAC	2×10W	1×10W	1800(Normal)/ 900(Emergency)	180min	6. 6(Lamp)/ 2.9(Emergency box)	class I, zone1 &zone2, zone21 &zone22	780×180×110	2×20W
BC5401-L2×20		2×20W	1×20W	3600(Normal)/ 1800(Emergency)	90min	10. 7(Lamp)/ 2.9(Emergency box)		1390×180×110	2×40W

*Equipped with explosion proof emergency box BXP01; only one tube lighting when emergency.

ABS Ex IECEx IP 66 Ta 50 Ta -25

■ Low installation height equipment area like petrochemical plants, chemical plants, pharmaceutical factory, polishing plant, etc.

■ EX Mark: Ex II 2G Ex db IIC T6 Gb
Ex II 2D Ex tb IIIC T80℃ Db
■ Cable Entry: M20×1.5, M25×1.5, NPT3/4",
NPT1/2", G3/4"

BXP01

ATEX Cert No.: EPT16 ATEX 2484 X
IECEx Cert No.: IECEx EUT 17.0012X

Type	Rated voltage (V)	Wattage (W)	Emergency duration (min)	Output voltage (V)	Net weight (kg)	Application	Size (mm)
BXP01	100~240VAC	30W	60min	220VDC	2.9	class I, zone1 &zone2, zone21 &zone22	238×222×106
		20W	90min				
		10W	180min				

■ Equipment area, stacking and stockyard, like petrochemical plants, chemical plants, pharmaceutical plants, etc.

■ EX Mark: Ex d IIB T6 Gb
Ex tD A21 IP66 T80℃
■ Cable Entry: G3/4"

Ex CE IP 66 Ta 45 Ta -20

BC9101A BC9101B

Type	Rated voltage (V)	Wattage (W)	Emergency wattage (W)	Emergency light output (lm)	Emergency duration (min)	Net weight (kg)	Size (mm)	Replaces MH
BC9101A-L25-15	100~240VAC	25W	15W	1800	120min	9	370×326×88	70W/ 35W
BC9101A-L40-15		40W	15W	1800				100W/ 35W
BC9101A-L60-15		60W	15W	1800				150W/ 35W
BC9101A-L25-25	100~240VAC	25W	25W	3000	70min	9	370×326×88	70W/ 50W
BC9101A-L40-25		40W	25W	3000				100W/ 50W
BC9101A-L60-25		60W	25W	3000				150W/ 50W
BC9101B-L15	100~240VAC	/	15W	1800	120min	9	370×326×88	/ 35W
BC9101B-L25		/	25W	3000	70min			/ 50W

■ Suitable for oil mining, refining, chemical industry, power plants and other dangerous places for working lighting.

■ EX Mark: Ex de IIB T5/T6 Gb
Ex tb Ⅲ C T80℃ Db
■ Cable Entry: G3/4 ″ ,NPT3/4″ ,M25×1.5

Ex

BC9105J

Type	Rated voltage (V)	Wattage (W)	emergency wattage(W)	light output(lm)	emergency duration(min)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9105J-L80-L5	100~240VAC	80W	5W	12800	≥180	5	class I, zone 1 &zone2, zone21 &zone22	346×273×115	150W-175W
BC9105J-L80-L10		80W	10W	12800	≥90				
BC9105J-L5		/	5W	/	≥180				
BC9105J-L10		/	10W	/	≥90				

*BC9105B with only emergency function

■ Suitable for oil mining, refining, chemical industry, power plants and other dangerous places for working lighting.

■ EX Mark: Ex nR IIC T6 Gc
Ex tb Ⅲ C T80℃ Db
■ Cable Entry: G3/4 ″ ,NPT3/4″ ,M25×1.5

Ex

BC9107J

Type	Rated voltage (V)	Wattage (W)	emergency wattage(W)	light output(lm)	emergency duration(min)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9107J-L80-L5	100~240VAC	80W	5W	12800	≥180	5	zone2, zone21 &zone22	346×273×111	150W-175W
BC9107J-L80-L10		80W	10W	12800	≥90				
BC9107J-L5		/	5W	/	≥180				
BC9107J-L10		/	10W	/	≥90				

*BC9107B with only emergency function

■ Suitable for emergency lighting to low installation height region in extreme climate, like offshore oil, chemical equipment platforms, tankers, ships, docks, piers, etc.

■ EX Mark: Ex II 2G Ex db e IIC T6/T5 Gb
Ex II 2D Ex tb IIIC T80℃/ T95℃ Db
■ Cable Entry: M20×1.5, NPT1/2" (P type/ S type)
M25×1.5, NPT3/4", G3/4" (P type)

Ex IECEx CE RoHS LM79 LM84 IP 66 Ta 50 Ta -25

BC9306AP/BP

BC9306AS/BS

ATEX Cert No.: EPT16 ATEX 2484 X
IECEx Cert No.: IECEx EUT 17.0011X

Type	Rated voltage (V)	Wattage (W)	Emergency wattage (W)	Emergency light output (lm)	Emergency duration (min)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9306AP-L40-15	100~240VAC	40W	15W	1800	120min	4.2	class I, zone1 &zone2, zone21 &zone22	Ø230×270	100W/ 35W
BC9306AP-L40-25			25W	3300	70min				100W/ 50W
BC9306BP-L15		/	15W	1800	120min				/ 35W
BC9306BP-L25			25W	3300	70min				/ 50W
BC9306AS-L40-15	100~240VAC	40W	15W	1800	120min	4.9	class I, zone1 &zone2, zone21 &zone22	245×260×270	100W/ 35W
BC9306AS-L40-25			25W	3300	70min				100W/ 50W
BC9306BS-L15		/	15W	1800	120min				/ 35W
BC9306BS-L25			25W	3300	70min				/ 50W

*The lamp can be matched with a lens: 40°, 60°, 80°, 100°, 200°, 60°×80°, 90°×110° CCT: 3000K, 4000K, 5000K.

TORMIN Emergency Lights

■ This product is widely used for low installation height equipment area like petrochemical plants,chemical plants,pharmaceutical factory,polishing plant ,etc.

■ EX Mark: Ex d II C T6 Gb
Ex tD A21 IP66 T80℃
■ Cable Entry: G3/4 "

Ex

BXP02

Type	Rated voltage (V)	Wattage (W)	Emergency wattage(W)	Emergency duration(min)	Rated capacity	Net weight (kg)	Size (mm)
BXP02A-L50-L5	100~240VAC	50W	5W	≥90min	7.4V 2600mAh	2.5	240×230×105.5
BXP02A-L40-L15/25		40W	15W/25W	≥180min/≥90min	14.8V 2600mAh		
BXP02B-L5/10		Max200W	5W/10W		7.4V 2600mAh		
BXP02B-L15/25		/	15W/25W		14.8V 2600mAh		

■ This product is widely used for emergency lighting in hazardous locations.

TM-ZFZD-E6W-BC5200

■ EX Mark: Ex d IIC T6 Gb
Ex tD A21 IP66 T80℃
■ Cable Entry: G3/4 "

Ex

TM-ZFZD-E6W-BC5200

Type	Rated voltage (V)	Wattage (W)	Emergency wattage(W)	Emergency duration(min)	Net weight (kg)	Application	Size (mm)
TM-ZFZD-E6W-BC5200	220VAC	2×3W	2×3W	≥90min	2.9	class I, zone 1 &zone2, zone21 &zone22	255×243×110

■ Suitable for plant platforms, equipment floor areas, main and auxiliary workshops, access roads, pipelines, combined stations, transfer stations, pump and valve sheds, tanks, material sample ports, stacks, silo rooms, warehouses, etc.

■ EX Mark: Ex d IIC T6 Gb
Ex tD A21 IP66 T85℃
■ Cable Entry: G3/4 "

Ex

TM-ZLZD-E40W-BC9302

Type	Rated voltage (V)	Wattage (W)	Emergency wattage(W)	Emergency duration(min)	Net weight (kg)	Application	Size (mm)
TM-ZLZD-E40W-BC9302	220VAC	40W	15W	90min	5	class I, zone 1 &zone2, zone21 &zone22	Φ240×220

■ This product is widely used for emergency lighting in hazardous locations.

■ EX Mark: Ex II 2G Ex db eb II C T6 Gb
Ex II 2D Ex tb III C T80℃ Db
■ Cable Entry: M25X1.5 G 3/4 NPT 3/4

Ex IECEx Ta 45/0 IP 66

BC4210

BC5210

Type	Rated voltage (V)	wattage (W)	Emergency duration(min)	Net weight (kg)	Size (mm)
BC4210	100～240V AC	1.5W	180min	3.5	373×165×64
BC5210		2W			

■ This product is widely used in emergency lighting in industrial areas and harsh environment

IP 66

TM-ZFZD-E6W-ZY5200

Type	Rated voltage (V)	wattage (W)	Emergency duration(min)	Net weight (kg)	Size (mm)
TM-ZFZD-E6W-ZY5200	220VAC	2×3W	≥90min	2.9	269×258×97

■ This product is widely used for power distribution room, switchboard, main control room of substation, high voltage room, meeting room, office and other indoor places.

ABS

ZY5321E

Type	Rated voltage (V)	Wattage (W)	Emergency wattage(W)	Emergency duration(min)	Light output(lm)	Net weight (kg)	Size (mm)	Replaces MH
ZY5321E-L36	200-240VAC	36W	/	/	5200	2	1212×72×67	70W~100W
ZY5321EJ-L36-L5			5W	180min		2.2		
ZY5321Ei-L36			/	/		2.1		

■ Power plants, substations, chemical plants, metallurgical plants and other indoor and outdoor emergency lighting.

■ Cable Entry: M16

CE RoHS IP 66 Ta 50 Ta -25

ZY8101A ZY8101B

Type	Rated voltage (V)	Wattage (W)	Emergency wattage (W)	Emergency light output (lm)	Emergency duration (min)	Net weight (kg)	Size (mm)	Replaces MH
ZY8101A-L25-15	100~240VAC	25W	15W	1800	120min	4.7	300×300×75	70W/ 35W
ZY8101A-L40-15		40W	15W	1800				100W/ 35W
ZY8101A-L60-15		60W	15W	1800				150W/ 35W
ZY8101A-L25-25		25W	25W	3000	70min			70W/ 50W
ZY8101A-L40-25		40W	25W	3000				100W/ 50W
ZY8101A-L60-25		60W	25W	3000				150W/ 50W
ZY8101B-L15		/	15W	1800	120min			/ 35W
ZY8101B-L25		/	25W	3000	70min			/ 50W

*ZY8101B-L15, ZY8101B-L25 only have emergency lighting function.

■ Suitable for workshop, power plant, tunnel and any other industrial area.

■ Cable Entry: G3/4 ", NPT3/4″ ,M25×1.5

IP 66 Ta 50 Ta -40

ZY8108J

Type	Rated voltage (V)	Wattage (W)	emergency wattage(W)	light output(lm)	emergency duration(min)	Net weight (kg)	Size (mm)	Replaces MH
ZY8108J-L80-L5	100~240VAC	80W	5W	12800	≥180	5	346×273×111	150W-175W
ZY8108J-L80-L10		80W	10W	12800	≥90			
ZY8108J-L5		/	5W	/	≥180			
ZY8108J-L10		/	10W	/	≥90			

■ Power plants, substations, chemical plants, metallurgical plants and other indoor and outdoor emergency lighting.

IP 66 Ta 50 Ta -25

ZY8810

Type	Rated voltage (V)	Wattage (W)	Emergency wattage (W)	Emergency light output (lm)	Emergency duration (h)	Net weight (kg)	Size (mm)	Replaces Fluorescent lamp
ZY8810-L12	100~240VAC	12W	6W	600	> 10	2	180×130×65	28W
ZY8810-L6		6W	4W	300				18W

*Auto emergency or manual emergency could be adjusted